



Enriched Uranium BUZZSAW

Drilling Specifications

Pin Position

<p>The Buzzsaw's 12:00 pin, relative to the CG, makes this ball driller friendly for right & leftand bowlers.</p>	<p>Turning the pin towards 3 O'clock, relative to the CG, will increase length.</p>	<p>Turning the pin towards 9 O'clock, relative to the CG, will decrease length.</p>	<p>Pin and distance from axis</p>
---	---	---	-----------------------------------

Drilling Recommendations

<p>Label</p> <p>Flare 8 Back-end 9</p>	<p>Pin Near Track</p> <p>Flare 2 Back-end 5</p>	<p>Stacked</p> <p>Flare 8 Back-end 8</p>	<p>CG Leverage</p> <p>Flare 6 Back-end 7</p>
<p>Pin In Label</p> <p>Flare 6 Back-end 8</p>	<p>Axis Leverage</p> <p>Flare 9 Back-end 6</p>	<p>1/2 Leverage</p> <p>Flare 7 Back-end 7</p>	<p>Notes</p> <ol style="list-style-type: none"> 1. Pos. side, finger, & top wt., increase length and back-end. 2. Neg. side, thumb, & bottom, decrease length and back-end. 3. Axis holes decrease flare and back-end reaction. 4. Pin-in balls decrease length. 5. Pin-out balls increase length and flip. 6. If the ending center of gravity is on your pin, starting CG, or on the same rotational plane as those, ball reaction is enhanced.